



Stainless Steel 177 PH Condition C Spring Wire

ASTM A313 type 631 & AMS 5678 (equivalent to EN10270-3 1.4568)

DIA mm	DIA inch
0.432	.017
0.457	.018
0.508	.020
0.559	.022
0.584	.023
0.610	.024
0.635	.025
0.660	.026
0.686	.027
0.711	.028
0.737	.029
0.762	.030
0.813	.032
0.838	.033
0.864	.034
0.889	.035
0.914	.036
0.940	.037
0.991	.039
1.041	.041
1.067	.042
1.092	.043
1.118	.044
1.143	.045
1.207	.0475
1.245	.049
1.295	.051
1.372	.054
1.397	.055
1.422	.056
1.448	.057
1.473	.058
1.499	.059
1.524	.060

DIA mm	DIA inch
1.588	.0625
1.651	.065
1.702	.067
1.727	.068
1.778	.070
1.829	.072
1.905	.075
1.930	.076
1.981	.078
2.032	.080
2.083	.082
2.108	.083
2.159	.085
2.184	.086
2.235	.088
2.286	.090
2.324	.0915
2.362	.093
2.388	.094
2.413	.095
2.489	.098
2.540	.100
2.565	.101
2.667	.105
2.769	.109
2.794	.110
2.845	.112
2.921	.115
2.997	.118
3.048	.120
3.175	.125
3.429	.135
3.505	.138
3.607	.142

DIA mm	DIA inch
3.759	.148
3.962	.156
4.115	.162
4.318	.170
4.369	.172
4.496	.177
4.750	.187
4.877	.192
5.258	.207
5.537	.218
5.944	.234
6.198	.244
6.350	.250
6.655	.262
7.163	.282
7.188	.283
7.417	.292
7.620	.300
7.772	.306
7.925	.312
8.407	.331
8.712	.343
9.195	.362
9.525	.375
10.008	.394
10.312	.406
11.100	.437
11.887	.468
12.700	.500
13.487	.531
14.275	.562
15.875	.625