



Stainless Steel 302 Spring Wire

ASTM A313 & AMS 5688 (equivalent to EN10270-3 1.4310)

DIA mm	DIA inch
0.152	.006
0.203	.008
0.254	.010
0.305	.012
0.330	.013
0.356	.014
0.381	.015
0.406	.016
0.432	.017
0.457	.018
0.483	.019
0.498	.0196
0.508	.020
0.533	.021
0.559	.022
0.584	.023
0.599	.0236
0.61	.024
0.635	.025
0.660	.026
0.686	.027
0.699	.0275
0.711	.028
0.737	.029
0.762	.030
0.787	.031
0.813	.032
0.840	.033
0.864	.034
0.889	.035
0.914	.036
0.94	.037

DIA mm	DIA inch
0.965	.038
0.991	.039
1.02	.040
1.04	.041
1.07	.042
1.09	.043
1.12	.044
1.14	.045
1.17	.046
1.21	.0475
1.22	.048
1.24	.049
1.27	.050
1.30	.051
1.32	.052
1.35	.053
1.37	.054
1.40	.055
1.42	.056
1.45	.057
1.47	.058
1.50	.059
1.52	.060
1.55	.061
1.57	.062
1.59	.0625
1.60	.063
1.63	.064
1.65	.065
1.70	.067
1.73	.068
1.75	.069

DIA mm	DIA inch
1.78	.070
1.80	.071
1.83	.072
1.85	.073
1.88	.074
1.91	.075
1.93	.076
1.98	.078
2.01	.079
2.03	.080
2.08	.082
2.11	.083
2.16	.085
2.18	.086
2.21	.087
2.24	.088
2.26	.089
2.29	.090
2.30	.0905
2.31	.091
2.32	.0915
2.34	.092
2.36	.093
2.39	.094
2.41	.095
2.46	.097
2.49	.098
2.51	.099
2.54	.100
2.59	.102
2.67	.105
2.77	.109