



X750 Spring Temper Wire

We keep all these diameters of **X750 Spring Temper Wire** in stock **so you don't have to!**

Specification is AMS 5699 soap coated. Other sizes available on request

0.2mm	.048"	.105"	.225"
0.25mm	1.25mm	2.7mm	.234"
0.3mm	.051"	2.8mm	6.0mm
0.35mm	1.3mm	3.0mm	.250"
0.4mm	.055"	.125"	6.5mm
0.5mm	1.4mm	3.2mm	.262"
.020"	1.5mm	3.3mm	7.0mm
0.6mm	1.6mm	.135"	.281"
.025"	.067"	3.5mm	7.5mm
0.68mm	1.7mm	.148"	.312"
0.7mm	1.8mm	3.8mm	8.0mm
0.75mm	.072"	.156"	.331"
.030"	1.9mm	4.0mm	.343"
0.8mm	2.0mm	.162"	9.0mm
.032"	.080"	4.2mm	.375"
.035"	2.1mm	.177"	10.0mm
0.9mm	.086"	4.5mm	.406"
1.0mm	2.2mm	.192"	.437"
.041"	2.3mm	5.0mm	.468"
1.1mm	.092"	.207"	12.0mm
.047"	2.4mm	5.5mm	.500"
1.2mm	2.5mm	.218"	.562"